

Lucerne safes

Certified burglary protection according to EN 1143-1 Class I

The classic and practical safe

Technical data :


- Multi-wall construction
- Thickness of the post 85 mm
- Filled with insulation material PEARLITE/ISOPLAN
- Central locking by bolts on four sides
- Door pivots on the inside
- Retractable handle and lock
- Device for floor and wall mounting

Standard finishes :

- Double bitted key lock includes two keys
- Removable shelves
- Light grey RAL 7035 or anthracite RAL 7016
- Door pivots: right or left

Options :

- Number combination lock mechanics
- Electronic lock
- Special colours



Lucerne 61403



TECHNO SAFE Coffres-forts

Avenue Industrielle 5, 1227 Carouge
+41 22 343 21 14
info@technosafe.ch / www.technosafe.ch

Type	Dimensions ext. (mm)			Dimensions int. (mm)			Weight/Vol Kg/litres	Shelves
	H	L	P	H	L	P		
Certified burglary protection according to EN 1143-1 Class I								
Lucerne 61402	336	496	410	230	404	291	80/27	1
Lucerne 61403	436	496	410	330	404	291	100/38	1
Lucerne 61404	536	496	410	430	404	291	117/50	1
Lucerne 61405	636	496	410	530	404	291	132/62	2
Lucerne 61406	736	496	410	630	404	291	152/74	2
Lucerne 61407	836	496	410	730	404	291	167/85	2
Lucerne 61408	1036	496	410	930	404	291	205/109	2
Lucerne 61409	1036	496	500	930	404	381	218/143	2
Lucerne 61410	1236	496	410	1130	404	291	233/132	2
Lucerne 61411	1236	496	500	1130	404	381	248/173	2