EW II Safe

Burglary protection certified according to EN 1143-1 Grad II

Enhanced security

Technical data:

- Double-walled body with special reinforcement
- Multi-wall door
- External hinges
- Door opening angle: 145°
- Protruding handle approx. 65 mm
- 2 devices for ground mounting
- Standard colour: Light grey RAL 7035



Finitions standard :

- High-security double-bit keyed lock
- 3 x 190 mm wrenches
- Adjustable shelves depending on the model
- Door pivot: right

Options:

- Additional shelf
- Indoor locker
- Additional anchorage device Ø 13 mm
- Door pivot on the left
- Alarm System Components (EMA)
- Additional attachment on the back
- Special RAL paint on request



EW II-62



EW II-120

Type	Ext dimensions (mm)			Int dimensions (mm)			Weight Vol	Shekves
	H	W	D	H	W	D	Kg/liters	Includes
Burglary protection certified according to EN 1143-1 Grad II								
EW II-62	620	570	520	540	490	360	280/95	1
EW II-84	840	570	520	760	490	360	345/134	1
EW II-105	1050	570	520	970	490	360	420/171	2
EW II-120	1200	570	520	1120	490	360	465/198	2
EW II-156	1560	810	540	1480	730	380	730/411	3
EW II-187	1870	810	540	1790	730	380	850/497	4

Handle Depth +65 mm

TECHNO SAFE Coffres-forts Sàrl
Avenue Industrielle 5, 1227 Carouge
+41 22 343 21 14
info@technosafe.ch / www.technosafe.ch