

CWS safes - CWS-F

Certified burglary protection according to EN 1143-1 Grad III

CWS-F: Certified fire protection according to EN 15659 LFS 60P

For a good night's sleep

Technical data :

- Fire test 60 minutes for paper (CWS-F models)
- Solid locking on all sides
- Multi-wall construction
- All sides reinforced with material extremely resistant
- Filled with heat-resistant material
- Sensitive points protected by additional reinforcements
- Shielding of the locking system
- Locking of the lock and bolts in test case of burglary by means of an informer lock
- Alarm pre-equipment
- Device for floor and wall mounting



CWS 1600 with bank compartments

Standard finishes :

- Double bitted key lock
Includes two keys
- Removable shelves
- Two-tone grey RAL 7035 and RAL 7045
- Door pivots: right or left
- CWS 1902 and CWS 1904 two-door

Options :

- Number combination lock mechanics
- Electronic lock
- Electronic lock with emergency key
- Electronic lock with redundancy (Paxos)
- From model 1600 upwards: available with bank compartments
- Available in modular version (CWS models from size 1000 upwards)
- Special colours
- Interior fittings according to the price list



TECHNO SAFE Coffres-forts

Avenue Industrielle 5, 1227 Carouge

+41 22 343 21 14

info@technosafe.ch / www.technosafe.ch

Type	Dimensions ext. (mm)			Dimensions int. (mm)			Weight/Vol Kg/litres	Shelves
	H	L	P	H	L	P		
Certified burglary protection according to EN 1143-1 Grad III								
CWS 0849	848	645	565	695	495	320	625/110	1
CWS 0850	848	810	725	695	660	480	865/220	1
CWS 1000	1003	810	725	850	660	480	1010/269	2
CWS 1200	1193	810	725	1040	660	480	1110/329	2
CWS 1600	1538	810	725	1385	660	480	1365/439	3
CWS 1901	1883	810	725	1730	660	480	1640/548	4
CWS 1903	1883	1110	725	1730	960	480	2030/797	4
CWS 1902	1883	1110	725	1730	960	480	2070/797	4
CWS 1904	1883	1415	725	1730	1265	480	2480/1050	4
CWS-F: Certified fire protection according to EN 15659 LFS 60P								
CWS-F 0850	848	810	725	695	660	480	865/220	1
CWS-F 1000	1003	810	725	850	660	480	1010/269	2
CWS-F 1200	1193	810	725	1040	660	480	1110/329	2
CWS-F 1600	1538	810	725	1385	660	480	1365/439	3
CWS-F 1901	1883	810	725	1730	660	480	1640/548	4
CWS-F 1903	1883	1110	725	1730	960	480	2030/797	4

Depth: + 60 mm for hinges