

PRO PLUS III safe

Certified burglary protection to EN 1143-1 Grad III

Fire protection with intumescent door seal

Fire protection certified to EN 15659 LFS 60 P (Model 3080 N)

Pro Plus III

Technical data :

- Multi-wall construction
- Multi-wall door
- Anti-drilling armor
- Lock and bolt blocking in the event of attack by bolt dislodger
- Three-way central locking
- Pull-out protection on hinge side
- Arrangement for floor and back mounting
- Fire protection with intumescent seal in the door

Standard finishes :

- Double-bit key lock (2 keys included)
- Removable shelves
- Dark gray
- Door pivots: right

Options :

- Paxos Advance lock
- Electronic lock
- Mechanical lock
- Key and mechanical lock
- Key lock and electronic lock
- Pre-installation for burglar alarm
- Interior lighting
- Special colors



3215 N



3080 N

Type	Dimensions ext. (mm)			Dimensions int. (mm)			Weight Vol	Shelf
	H	W	D	H	W	D	Kg/liters	Includ
Certified burglary protection to EN 1143-1 Grad III								
3070 N	600	535	464	509	455	305	275/71	1
3080 /0***	659	680	620	509	530	385	430/104	1
3095 N	785	535	464	694	455	305	340/96	1
3175 N	955	610	544	864	530	385	480/176	2
3215 N	1135	610	544	1044	530	385	550/213	2
3285 N	1490	610	544	1399	530	385	660/285	3
3395 N	1490	760	574	1399	680	415	830/395	3
3560 N	1850	840	580	1759	760	421	1057/563	4
3820 N	1850	1190	580	1759	1110	421	1346/822	4

*** Fire protection certified to EN 15659 LFS 60 P (Model 3080 N)



TECHNO SAFE Coffres-forts

+41 22 343 21 14

info@technosafe.ch / www.technosafe.ch