

Burglary protection certified according to EN 1143-1 Grad II

IKARO

Technical data:

- Massive locking on all sides
 - Multi-wall construction
 - 45 mm thick walls
 - All sides reinforced with
- Extremely durable
- Anti-unhinged hinges
 - Anti-drilling shielding
 - Device for floor and wall mounting



Standard finishes:

- Double-bit keyed lock
- Colour: RAL 7021
- Door pivots: right

Options:

- Electronic lock
- Electronic lock + key
- Mechanical lock
- Mechanical lock + key
- Additional shelf
- Internal safe



IKARO 45



IKARU 110



TECHNO SAFE Safes

Avenue Industrielle 5, 1227 Carouge

+41 22 343 21 14

info@technosafe.ch / www.technosafe.ch

Type	External dimensions (mm)			Dimensions int. (mm)			Weight/Vol	Shelves
	H	W	D	H	W	D	Kg/liters	Includ
Burglary protection EN 1143-1 Grad II								
SECTION 45	450	500	480	360	410	330	115/48	1
SECTION 62	620	500	480	530	410	330	135/71	1
SECTION 85	850	600	550	760	510	400	205/155	2
SECTION 110	1100	600	550	1010	510	400	250/206	2
SECTION 145	1450	600	550	1360	510	400	325/277	3
+ 30 mm for the handle								