

CLE IV Series Safe

Burglary protection certified according to EN 1143-1 Grad IV

Fire protection certified according to LFS 15659 30 P

Robust

Technical data:

- Door equipped with a solid locking system
- Four-sided closure
- Protective layer of the trunk and door with 60 mm thick fortification concrete
- 12 rotating active bolts with a diameter of 25 mm
- Patented burglar-resistant construction
- Anti-drilling shielding
- Lock and bolt locks in case Whistleblower Lock Attack
- Adjustable shelves
- Device for floor and wall mounting
- Colour: White or charcoal grey

Standard finishes:

- 2 x Double Bit Key Locks
Included: 4 keys
- With or without interior trunk
- Door pivot: right

Options:

- Electronic lock and key lock
- 2 x electronic lock
- 2 x Electronic lock with emergency key
- Mechanical lock and key lock
- Additional shelf
- Indoor locker



CLE IV.67 Combi



CLE IV.52 KE

Type	Ext. dimensions (mm)			Int. dimensions (mm)			Weight Vol	Shelve
	H	W	D	H	W	D	Kg/liters	Incl.
Burglary protection certified according to EN 1143-1 Grad IV								
CLE IV.52	520	500	470	400	380	280	260/44	1
CLE IV.67	670	570	570	550	450	380	390/97	2
CLE IV.82	820	620	570	700	500	384	500/137	3
CLE IV.97	970	620	570	855	500	384	580/166	3
CLE IV.112	1120	670	570	1000	550	384	690/215	4
CLE IV.127	1270	670	570	1150	550	384	760/247	4
CLE IV.142	1420	670	670	1300	550	490	920/350	4
CLE IV.152	1520	770	670	1400	650	484	1050/446	6

Depth +60 mm for the handle



TECHNO SAFE Safes

Avenue Industrielle 5, 1227 Carouge

+41 22 343 21 14

info@technosafe.ch / www.technosafe.ch